



### STANDARD FEATURES

- Rear-mount frame
- For openings in 1/2" (12.7 mm) or 5/8" (15.9 mm) drywall walls and ceiling
- Concealed aluminum frame, hardware and mechanical touch latch
- Factory installed moisture/ mold resistant drywall inlay
- Frame acts as finishing bead
- 1/16" perimeter gap
- Virtually invisible finishing
- Air tight with EPDM rubber perimeter gasket
- Superior acoustics with air tight seal and mass of drywall inlay
- Fully removable door leaf
- Free-pivot hinge and safety cable

**BUY DIRECT from BAUCO for best pricing and shortest lead time.**

**Size**  
\_\_\_\_ " Width(X) x \_\_\_\_ " Length (Y)

**Thickness**  
 1/2"  
 5/8"

**Application**  
 Wall  
 Ceiling

### Latch Options

- (Standard) Mechanical Touch Latch  
 Slotted Cam  
 Torx Cam  
 Keyed Lock

### Inlay Options

- (Standard) Drywall  
 Acoustic Board  
 Plywood

- Tile Backer Drywall  
 Imperial Blue Board  
 Double Layer

### Time Saving Option

- Paint-ready Finish

**Project:** \_\_\_\_\_  
**Client:** \_\_\_\_\_  
**Approved by:** \_\_\_\_\_  
**Date:** \_\_\_\_\_

