



STANDARD FEATURES

- Rear-mount frame
- For openings in 1/2"(12.7 mm) or 5/8"(15.9 mm) drywall walls and ceiling
- Concealed aluminum frame, hardware and mechanical touch latch
- Factory installed moisture/ mold resistant drywall inlay
- Frame acts as finishing bead
- 1/16" gap between frame and door leaf
- Virtually invisible finishing
- EPDM rubber perimeter gasket
- Good sound control with seal and mass of drywall inlay
- Fully removable door leaf with clip action hinge release
- Steel single pivot pin hinge and safety cable

Standard Sizes

(Custom sizes from 8 x 8" to a maximum 24 x 36". For Larger openings use double door design or the BAUCO XL or BAUCO Plus II.)

Access Panel Size (Clear Opening)		Weight	
Inch	mm	lbs-1/2"	lbs-5/8"
8 x 8"	203 x 203mm	2.5	2.9
10 x 10"	254 x 254mm	3.1	3.8
12 x 12"	305 x 305mm	3.8	4.7
14 x 14"	356 x 356mm	4.5	5.8
16 x 16"	406 x 406mm	5.3	7
18 x 18"	457 x 457mm	6.2	8.3
20 x 20"	508 x 508mm	7.2	9.8
24 x 24"	610 x 610mm	9.4	12.9
24 x 36"	610 x 914mm	12.8	18.2

BUY DIRECT from BAUCO for best pricing and shortest lead time.

Size _____ " Width(X) x _____ " Length(Y)

Thickness
 1/2"
 5/8"

Application
 Wall
 Ceiling

Latch Options
 (Standard) Mechanical Touch Latch
 Slotted Cam
 Torx Cam
 Keyed Lock

Inlay Options
 (Standard) Drywall
 Acoustic Board
 Imperial Blue Board
 Plywood
 Double layer Drywall

Time Saving Option
 Paint-ready Finish (Factory-primed door leaf. Ready to paint)

Project: _____
 Client: _____
 Approved by: _____
 Date: _____



1.877.592.0033 | info@bauco.com | bauco.com
 834 Devonshire Road Victoria, BC, Canada V9A 4T4